# HIT HOFMAN S.R.O.

**Road safety first** 


# Light arrow SS15 LED with frame

Light arrow is a signalling device used for maintenance vehicles, gritters, road sweepers, marking vehicles and trailers, or it can be used for indicating road works and the direction of its drive-around. This light arrow is also described as **Light arrow and cross type B**, warning arrow or signalling arrow. The light arrow can be supplemented by two warning lamps or beacons of different types to improve the warning effect.

#### > 15 LED lamps ø200mm EN 12352 L8H

- main advantage of the light arrow with 15 lamps is a more visible symbol of cross
- electronics automatically reduce lamp luminous intensity at night and includes reverse polarity protection
- moreover, the electronics protect the battery from deep discharge by disconnecting the light arrow symbols and possibly also the upper warning lamps depending on the current battery status
- remote control with 15m cable for control and optical check of the function modes
- the light arrow has the following modes: arrow to the left, arrow to the right and cross
- all operational information are clearly displayed on the remote control
- standard 10m power supply cable to be installed on the vehicle (upon request, 4m power supply cable with battery clips)
- light arrow can easily be attached to a profile with a maximal width 40mm
- two warning lamps or beacons of different types can be added to the light arrow to improve the warning effect

Technical data for consumption refer to the light arrow only.











LIGHT ARROW SS15 LED WITH VLS-2 SUPPLIED FROM BATTERY 12V/180AH KEEP FLASHING NONSTOP FOR UP TO 6 DAYS

### www.hit-hofman.cz

HIT HOFMAN, s.r.o. Pražská 333 CZ-252 44 Psáry Tel: +42 Copyright © 2025 HIT HOFMAN, s.r.o.

Tel: +420 241029960

E-mail: hit@hit-hofman.cz 3.4.2025 1 / 2

# HIT HOFMAN S.R.O.

**Road safety first** 

### **TECHNICAL DATA**

Power supply	12/24V=
Current consumption 12V=	day 1,0A night 0,4A
Average consumption 12V=	16,4Ah / 24 hours
Current consumption 24V=	day0,55A night0,23A
Average consumption 24V=	9,2Ah / 24 hours
Flashing frequency	60/min.
Dimensions (WxHxL)	1370x1445x171mm
Weight	25,9kg

#### PRODUCTS

Order no.	Product name	Quantity
1-120-255020	Light arrow SS15 LED with frame	1 pc.

### ACCESSORIES

Order no.	Product name	Quantity
1-140-905052	SS - Set of two warning lamps VLS-2 LED	1 рс.
1-140-905022	SS - Set of two signalling lamps SLS-2 LED	1 pc.
1-140-910032	SS - Adapters for beacons MO-2	1 pc.
1-035-020200	Wireless remote control SS15-2_02 MZS RADIO	1 pc.
3-580-10000100	Remote control bracket DO-082	1 pc.

## www.hit-hofman.cz

Tel: +420 241029960

E-mail: hit@hit-hofman.cz 3.4.2025 2/2