

NZSP-1_01 Light arrow SS13-L LED

Light arrow is a set to be installed on warning boards for indicating road works. This light arrow is also described as **Light arrow and cross type B**, warning arrow or signalling arrow.

- > **2 warning LED lamps** ø300mm **EN 12352 L9H**
- > **13 LED lamps** ø200mm **EN 12352 L8H**
- > electronics automatically reduce lamp luminous intensity at night and includes reverse polarity protection
- > moreover, the electronics protect the battery from deep discharge by disconnecting the light arrow symbols and possibly also the upper warning lamps depending on the current battery status
- > the light arrow symbols are switched on automatically depending on the position of the white arrow on the blue round traffic sign
- > the light arrow has the following modes: arrow to the left, arrow to the right and cross



TECHNICAL DATA

Power supply	12/24V=
Current consumption 12V=	day 1,76A night 0,65A
Average consumption 12V=	30Ah / 24 hours
Current consumption 24V=	day 1,0A night 0,37A
Average consumption 24V=	16,3Ah / 24 hours
Flashing frequency	60/min.
Weight	15kg

TRAILER WITH THE LIGHT ARROW
SS13-L LED SUPPLIED FROM ONE
BATTERY 12V/180AH KEEPS
FLASHING NON-STOP FOR UP TO 6
DAYS

PRODUCTS

Order no.	Product name	Quantity
1-035-005025	NZSP-1_01 Light arrow SS13-L LED	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-035-005520	NZSP-1_01 Extension of light arrow to SS15 LED	1 pc.
1-035-200010	NZSP-1_01 Motor-operated arrow rotation MOS 12V	1 pc.

1-035-201010	NZSP-1_01 Motor-operated board lifting MZS 12V	1 pc.
1-035-202010	NZSP-1_01 Motor-operated board lifting and arrow rotation MZS+MOS 12V	1 pc.
1-035-020200	Wireless remote control SS15-2_02 MZS RADIO	1 pc.