

## Signalling halogen lamp SHS10-1.K cinch

Signalling lamp for quick highlighting of an obstacle in the traffic (accident, parked vehicle) or notifying of existing traffic signs.

- > **halogen lamp** ø200mm **EN 12352 L8H**
- > lamp flashing in **synchronous mode**
- > electronics automatically reduce luminous intensity at night
- > moreover, the electronics include reverse polarity protection and protect the battery from deep discharge
- > **1,5m power supply cable with cinch connector**
- > the lamps can be attached to a **profile of ø43mm or 40x40mm**



### TECHNICAL DATA

Power supply	12V=
Current consumption 12V=	day 0,32A night 0,20A
Average consumption 12V=	6,1Ah / 24 hours
Flashing frequency	44/min.
Dimensions (WxHxL)	200x245x145mm
Weight	0,95kg



HALOGEN LAMP SUPPLIED FROM  
BATTERY 12V/7AH KEEPS FLASHING  
NONSTOP FOR UP TO 26 HOURS

### PRODUCTS

Order no.	Product name	Quantity
1-220-210011	<b>Signalling halogen lamp SHS10-1.K cinch</b>	1 pc.

### ACCESSORIES

Order no.	Product name	Quantity
1-220-900100	<a href="#">Switch for lamps SS-x</a>	1 pc.
2-890-020010	<a href="#">Battery for SS 12V/7Ah cinch</a>	1 pc.
2-045-090010	<a href="#">Adapter Z4/lamp 60/40</a>	1 pc.

2-040-015010	<a href="#">Delineator panel HIT-1.L arrow 60/60</a>	1 pc.
2-040-015020	<a href="#">Delineator panel HIT-1.LP arrow 60/60</a>	1 pc.
2-040-015040	<a href="#">Delineator panel HIT-1.PP arrow 60/60</a>	1 pc.
2-050-002000	<a href="#">Base plate HIT-BAT</a>	1 pc.