

Signalling halogen lamps with bracket 12V/24V=

Signalling lamps for enhanced road safety. Especially attached to highlight traffic signs, lane closure markers and roadblocks (barriers).

- > 1 to 3 halogen lamps \varnothing 200mm **EN 12352 L8H**
- > lamps flashing in **synchronous** or asynchronous mode
- > electronics automatically reduce luminous intensity at night
- > moreover, the electronics include reverse polarity protection and protect the battery from deep discharge
- > **5m power supply cable with battery terminals**, 3m length between each lamp
- > the lamps can be attached to a **profile of \varnothing 43mm or 40x40mm**



Technical data in the chart refer to one signalling lamp.

TECHNICAL DATA

Power supply	12/24V=
Current consumption 12V=	day 0,64A night 0,40A
Average consumption 12V=	12,2Ah / 24 hours
Current consumption 24V=	day 0,36A night 0,22A
Average consumption 24V=	6,85Ah / 24 hours
Flashing frequency	44/min.
Dimensions (WxHxL)	200x245x145mm
Weight	0,95kg



SET OF THREE L8H HALOGEN LAMPS
SUPPLIED FROM BATTERY 12V/180AH
KEEPS FLASHING NONSTOP FOR UP
TO 5 DAYS

PRODUCTS

Order no.	Product name	Quantity
1-220-200021	Signalling halogen lamp SHSU20-1.K	1 pc.
1-220-200022	Twin signalling halogen lamp SHSU20-2.K	1 pc.
1-220-200023	Triple signalling halogen lamp SHSU20-3.K	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-220-900100	Switch for lamps SS-x	1 pc.
2-890-010020	Battery 12V/180Ah	1 pc.
1-110-100100	Small lockable battery box UZA-M/M	1 pc.
1-180-010010	Collapsible barrier LZ-Z2-1	1 pc.
1-180-010030	Collapsible barrier LZ-Z2-2-SS	1 pc.