

Signalling lamp SLSU-1.K LED cinch

Signalling lamp for quick highlighting of an obstacle in the traffic (accident, parked vehicle) or notifying of existing traffic signs.

- > **LED lamp** ø200mm **EN 12352 L8H**
- > lamp flashing in **synchronous mode**
- > electronics automatically reduce luminous intensity at night
- > moreover, the electronics include reverse polarity protection and protect the battery from deep discharge
- > **1,5m power supply cable with cinch connector**
- > the lamps can be attached to a **profile of ø43mm or 40x40mm**



TECHNICAL DATA

Power supply	12V=
Current consumption 12V=	day 0,11A night 0,03A
Average consumption 12V=	1,67Ah / 24 hours
Flashing frequency	60/min.
Dimensions (WxHxL)	200x245x145mm
Weight	0,95kg



LED LAMP SUPPLIED FROM BATTERY
12V/7AH KEEPS FLASHING NONSTOP
FOR UP TO 100 HOURS

PRODUCTS

Order no.	Product name	Quantity
1-220-215011	Signalling lamp SLSU-1.K LED cinch	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-220-900100	Switch for lamps SS-x	1 pc.
2-890-020010	Battery for SS 12V/7Ah cinch	1 pc.
2-045-090010	Adapter Z4/lamp 60/40	1 pc.

2-040-015010	Delineator panel HIT-1.L arrow 60/60	1 pc.
2-040-015020	Delineator panel HIT-1.LP arrow 60/60	1 pc.
2-040-015040	Delineator panel HIT-1.PP arrow 60/60	1 pc.
2-050-002000	Base plate HIT-BAT	1 pc.