

## Warning board NZSP-1.1\_20 LED R20 64x128RGB

Warning board for flexible indication of road works is primarily used on highways and dual carriageways. The high intensity LEDs and high-quality optics enable very good visibility in all weather conditions. The warning board is attached to the loading area of the vehicle.

- > warning board must be firmly attached to the loading area of the vehicle
- > warning board can be loaded using a forklift
- > it has a lockable battery box (WxHxL) 400x350x1660mm for two batteries with a capacity of up to 12V/230Ah
- > LED board can be lifted/lowered by a linear actuator that has a bolt enabling manual lifting or lowering in case of failure or emergency, the LED board frame is secured against wind pressure in the operating position
- > LED board contains high-intensity LEDs and high-quality optics with anti-static lens
- > LED board is **approved according to EN 12966-1**
- > LED board consists of full-colour RGB LEDs **64x128pixel, 20mm pixel pitch**, the upper part can display 64x54pixel (with a) maximum symbol size 1280x1080mm, the lower part can display 64x74pixel (with a) maximum symbol size of 1280x1480mm
- > LED luminous intensity is controlled automatically depending on the surrounding light or it can be controlled manually
- > wireless (radio) remote control with graphic display shows all operational information, it can also be connected with cable
- > symbols on both LED boards **are user programmable**, new symbols or texts can easily be created and uploaded into the device
- > total capacity of the system is **1500 traffic sign symbols, other symbols or texts**
- > every symbol and animation can be combined with every text
- > to attract more attention, the symbols can be **flashing 15-60 times a minute**, two symbols can alternate, or a **simple animation** can be displayed



OTHER SIZES AND PARAMETERS OF THE LED BOARDS AVAILABLE UPON REQUEST

### WARNING BOARD VARIANTS

- > remote monitoring and controlling of the warning board via GPRS and GPS location tracking

▶ power supply from fuel cell battery charger

## TECHNICAL DATA

Weight	400kg
Overall length	3122mm
Overall width	1700mm
Transport height	1534mm
Operational height	3755mm

## PRODUCTS

Order no.	Product name	Quantity
1-030-008870	<b>Warning board NZSP-1.1_20 LED R20 64x128RGB</b>	1 pc.

## ACCESSORIES

Order no.	Product name	Quantity
1-035-015052	<a href="#">NZSP-1_01 Set of two warning LED lamps VLSU-2 LED</a>	1 pc.
2-890-010020	<a href="#">Battery 12V/180Ah</a>	1 pc.
2-895-092300	<a href="#">ZSP_01 Battery charger 12V/30A</a>	1 pc.